| GEZE UK - SPECIFICATION SHEET 1 | | RWA (Smoke & Heat Extraction equipment) |
|---------------------------------|---|--|
| 1 | Casement dimension (in mm) | Width:mm Height:mm |
| 2 | Casement weight (in Kg) | kg: |
| 3 | Type of window | □ bottom hung casement □ top hung casement □ side hung casement □ top and bottom centre hung casement □ left and right centred hung casement |
| 4 | Opening type | ☐ inward opening ☐ outward opening |
| 5 | Shape of casement | rectangular triangular inclined dome arched round arched flat arched |
| 6 | Number of RWA casements | qty. |
| 7 | Number of ventilator groups | qty. |
| 8 | Location of casements (high level) | ☐ Built vertical into façade☐ Built into inclined façade☐ Built into the roofing |
| | (low level) | ☐ Built vertical into façade☐ Built into inclined façade☐ Built into the roofing |
| 9 | Required free smoke extraction area in metre ² | m²/Ventm² Total |
| 10 | Required opening travel in mm (alt in degrees) | mm: |
| 11 | Reveal depth in mm (if applicable) | mm: |
| 12 | Mullion transom details | ☐ Yes ☐ No (if yes, please fax details) |
| 13 | Required RWA type | ☐ Electric drive (E250, RWA 100/110E, RWA E205/206 + GEZE fanlight opener) |
| 14 | Colours | ☐ Standard colours (EV1 silver colour, dark bronze, white RAL 9016)☐ Special colours (RAL, HEWI, etc) |
| 15 | Enclosures (e.g. technical drawing or rough draft) | ☐ Yes ☐ No |